



UP TO 32 ADDRESSABLE TEMPERATURE SENSORS ON A SINGLE STRING

Temperature sensor series TS-32 provides reliable means to monitor temperature at various locations in boreholes, dam embankments, landfills, levees.

Description

The Model TS-32 temperature string consists of a 4-wire, 22 AWG polyurethane cable with individual "Smartwire" sensors distributed along its length. The string can be attached to a structure, or buried in concrete or in the ground.

The temperature strings are customized according to user needs. The total length of the string as well as spacing (regular or not) are required when placing an order. Please refer to the ordering information for the different options.

Readings can be obtained with portable readout box (directly in degree Celsius), or with a data acquisition system model SENSLOG equipped with a module TS-32i that allows it to read "Smartwire" sensors.

Key Features

- Available in various configurations
- Digital sensors (BUS)
- Reliable & sensitive
- Up to 32 sensors on a single cable
- Minimum spacing: 250mm
- Pre-Assembled
- Water tightness: 2000 kPa

Applications

- Levees
- Landfills
- Boreholes
- Dam embankments

Specifications

MODEL	TS-32
Range*	-40 to + 80°C
Accuracy	±0.4°C between -20°C to 70°C
Resolution	0.01 °C
Sensor	Digital
Water tightness	4550 kPa (650psi)
Minimum spacing	200 mm
Maximum bead diameter	17 mm
Cable	IRC-41A-PU (Polyurethane sheeting)

* Temperature range of cable must be considered (e.g. - to +80°C for the IRC cable)

Ordering Information

Please specify:

- spacing
- Cable length

Optional Accessories

- SDI-12 / Smartwire interface
- Readout unit

Roctest Ltd,
680 Birch Street
St-Lambert, Quebec
Canada J4P 2N3

Phone +1 450 465 1113
Fax. +1 450 465 1938

Email info@roctest.com
Web www.roctest.com